

**DATI TECNICI**

RPM (tachimetro):

Per motori a 2 e 4 cilindri

RPM4 600 - 4000 RPM

RPM4 600 - 12000 RPM (x10 RPM)

RPM2/DIS 300 - 4000 RPM

RPM2/DIS 300 - 6000 RPM (x10 RPM)

Angolo Dwell: 4-8 CYL

Tensione DC: 400mV-4/40/400/1000V

Tensione AC: 4/40/400/700V

Corrente DC: 40/400mA-4/20A

Corrente AC: 40/400mA-4/20A

Resistenza: 400Ω-4/40/400kΩ-4/40MΩ

Capacità: 40/400nF-4/40/100μF

Frequenza: 5/50/500Hz-50/500-10MHz

Duty Cycle: 0.1 - 99,9%

Ampiezza pulsazioni: 1 - 10ms

Prova diodi: Corrente test 0,3mA

Continuità: <150Ω - Corrente test <0,3mA

Display: LCD ad alto contrasto 4 digit retro-illuminato

Sovratensione: Categoria II 1000V

Autospegnimento: 30 minuti

Alimentazione: 1 batteria 9V (inclusa)

Pinza induttiva (inclusa)

2 Puntali (inclusi)

Custodia morbida in tela (inclusa)

Manuale d'uso



017600005

art.

1760DGT



kg

1,1