


• Misure in pollici



art.	"	L mm	54,0	S mm	g	
000780910	78BA-AS 1.1/4	1.1/4	177	54,0	23,5	570
000780912	78BA-AS	1.7/16	208	60,0	26,5	780
000780914	78BA-AS 1.5/8	1.5/8	225	67,0	26,0	950
000780916	78BA-AS	1.13/16	243	74,0	28,0	1235
000780918	78BA-AS 2	2	254	78,0	28,5	1500
000780920	78BA-AS	2.3/16	264	84,0	30,0	1685
000780922	78BA-AS 2.3/8	2.3/8	275	91,5	30,0	1960
★ 000780924	78BA-AS	2.9/16	286	99,5	31,5	2400
★ 000780926	78BA-AS	2.15/16	311	112,5	33,5	3110
★ 000780928	78BA-AS 3.1/8	3.1/8	325	118,0	35,5	3500
★ 000780930	78BA-AS 3.1/2	3.1/2	355	130,0	39,0	4600



Questo prodotto è in lega beryllio-coppia (Cu-Be) e non deve essere usato in ambienti con presenza di scintille o con apparecchiature che producano scintille.  
 Cu-Be non è adatto per l'uso in ambienti con presenza di scintille.  
 This apparatus body cannot be used in contact with equipment that produces sparks or arcs.  
 Copper-beryllium must not be used in the presence of sparks, equipment that may generate sparks.