

**DATI TECNICI**



- coefficiente di sicurezza: 4

**CERTIFICATI DISPONIBILI**

- Specifica Prodotto

- Rapporto di Prova tipo 2.2 UNI EN10204



		art.	 Ø mm			
	<b>081200015</b>	8120 12,8 x 6,8	1,5	10	8	150
	<b>081200016</b>	8120 1,6X150	1,6	12	15	150
	<b>081200022</b>	8120 2,2X75	2,2	14	25	75
	<b>081200027</b>	8120 2,7X75	2,7	16	40	75
	<b>081200030</b>	8120 3,0X75	3,0	17	55	75
	<b>081200034</b>	8120 3,4X60	3,4	18	100	60
	<b>081200038</b>	8120 3,8X50	3,8	19	110	50
	<b>081200044</b>	8120 4,4X40	4,4	20	200	40
	<b>081200048</b>	8120 4,8X30	4,8	21	250	30
	<b>081200055</b>	8120 5,5X25	5,5	22	300	25
	<b>081200058</b>	8120 5,8X25	5,8	23	310	25
	<b>081200065</b>	8120 6,5X25	6,5	24	400	25
	<b>081200075</b>	8120 7,5X20	7,5	26	550	20
*	<b>081200080</b>	8120 8,0X25	8,0	27	600	25
*	<b>081200090</b>	8120 9,0x25	9,0	28	800	25
*	<b>081200100</b>	8120 10,0X20	10,0	30	1000	20
*	<b>081200120</b>	8120 12,0X15	12,0	32	1400	15
	<b>081200070</b>	8120 7,0x25	7,0	25	450	25