

8156




brache per sollevamento 3t giallo nastro piatto a due strati, asole rinforzate, poliestere alta tenacità (PES)

CE

UNI EN 1492-1



art.	art.	L m		
081560010	8156 1-T3	1	90	3
081560015	8156 1,5-T3	1,5	90	3
081560020	8156 2-T3	2	90	3
081560025	8156 2,5-T3	2,5	90	3
081560030	8156 3-T3	3	90	3
081560035	8156 3,5-T3	3,5	90	3
081560040	8156 4-T3	4	90	3
081560050	8156 5-T3	5	90	3
081560060	8156 6-T3	6	90	3
081560080	8156 8-T3	8	90	3
081560100	8156 10-T3	10	90	3
081560120	8156 12-T3	12	90	3

				$\beta = 0^\circ + 45^\circ$	$\beta = 45^\circ + 60^\circ$
30	1 t	0,8 t	2 t	1,4 t	1 t
60	2 t	1,6 t	4 t	2,8 t	2 t
90	3 t	2,4 t	6 t	4,2 t	3 t
120	4 t	3,2 t	8 t	5,6 t	4 t
150	5 t	4,0 t	10 t	7,0 t	5 t
180	6 t	4,8 t	12 t	8,4 t	6 t
240	8 t	6,4 t	16 t	11,2 t	8 t
300	10 t	8,0 t	20 t	14,0 t	10 t