

P801

- Lime rotative - cilindrico senza spallamento
- Frässtift- Zylinder ohne Stirnverzahnung
- Stiffrees - Cilindrisch zonder kopvertanding
- Lime rotative - Cylindrique sans coupe en bout

brasato su 6.00 mm
 Gelötet, wenn der Kopfdurchmesser größer 6 mm ist
 > Ø 6mm gesoldeerd
 Brasée au-dessus de 6,00 mm

P801C

P801; P801C	▪	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2.1	2.2	2.3	2.4	3.1	3.2	3.3	3.4	4.1	4.2	
		4.3	5.1	5.2	5.3	6.2	6.3	6.4	9.1											
	•	6.1																		

P801	HM	A					DC	
P801C	HM	A				TAIN	DC	



d_1 Ø mm	d_2 Øh ₇ mm	l_2 mm	l_1 mm	P801	P801C
3.00	3	14	38	P8013.0X3.0 ¹⁾	P801C3.0X3.0 ¹⁾
6.30	3	12.7	45	P8016.3X3.0	
6.00	6	18	50	P8016.0X6.0 ¹⁾	P801C6.0X6.0 ¹⁾
8.00	6	19	64	P8018.0X6.0	P801C8.0X6.0
9.60	6	19	64	P8019.6X6.0	P801C9.6X6.0
12.70	6	25	70	P80112.7X6.0	P801C12.7X6.0
16.00	6	25	70	P80116.0X6.0	

¹⁾ d2 tolleranza h6 / d2 toleranz h6 / d2 tolerantie h6 / d2 tolérance h6