

- A951**
- Punta serie extra lunga attacco conico
  - Spiralbohrer MK, extra lang
- A952**
- Extra lange spiraalboor met morseconus
  - Foret queue cône morse - Extra long

A951; A952

▪	1.1	1.2	1.3																
•	1.4	1.5	1.6	2.1	2.2	2.3	3.1	3.2	3.3	3.4	4.1	4.2	4.3	5.1	5.2	5.3	6.1	6.2	
	6.3	6.4	7.1	7.2	7.3	7.4	8.1	8.2	8.3	9.1									

<b>A951</b>	HSS	DIN 1870/1	15XD	130°	ST		W			
<b>A952</b>	HSS	DIN 1870/2	20XD	130°	ST		W			



$d_1$ $\varnothing h_8$ mm	$d_1$ decimal Inch	$l_2$ mm	$l_1$ mm	MK	A951	A952
8.00	0.3150	210	330	1		A9528.0
8.50	0.3346	210	330	1		A9528.5
9.00	0.3543	220	345	1		A9529.0
10.00	0.3937	185	285	1	A95110.0	
10.00	0.3937	235	360	1		A95210.0
10.50	0.4134	235	360	1		A95210.5
11.00	0.4331	195	300	1	A95111.0	
11.00	0.4331	250	375	1		A95211.0
11.50	0.4528	250	375	1		A95211.5
12.00	0.4724	205	310	1	A95112.0	
12.00	0.4724	260	395	1		A95212.0
12.50	0.4921	205	310	1	A95112.5	
12.50	0.4921	260	395	1		A95212.5
13.00	0.5118	205	310	1	A95113.0	
13.00	0.5118	260	395	1		A95213.0
13.50	0.5315	220	325	1	A95113.5	
13.50	0.5315	275	410	1		A95213.5
14.00	0.5512	220	325	1	A95114.0	
14.00	0.5512	275	410	1		A95214.0
14.50	0.5709	220	340	2	A95114.5 <sup>5)</sup>	
14.50	0.5709	275	425	2		A95214.5 <sup>6)</sup>
15.00	0.5906	220	340	2	A95115.0 <sup>5)</sup>	
15.00	0.5906	275	425	2		A95215.0 <sup>6)</sup>
15.50	0.6102	230	355	2	A95115.5 <sup>5)</sup>	
15.50	0.6102	295	445	2		A95215.5 <sup>6)</sup>
16.00	0.6299	230	355	2	A95116.0 <sup>5)</sup>	
16.00	0.6299	295	445	2		A95216.0 <sup>6)</sup>
16.50	0.6496	230	355	2	A95116.5 <sup>5)</sup>	

<sup>5)</sup> < 15xD  
<sup>6)</sup> < 20xD  
 110