

# B301

- Alesatore a mano per fori di spine coniche
- Hand-Kegelreibahle, gerade genutet
- Pengat handruimer
- Alésoir à main conique

B301	▪	1.1	1.2	1.3	1.4	2.1	3.1	4.1	6.2										
	•	1.5	1.6	2.2	2.3	3.2	3.3	3.4	4.2	4.3	5.1	6.1	6.3	6.4	7.1	7.2	7.3	7.4	8.2

B301 HSS 1:48



nom Ø	d <sub>1</sub> Ø mm	l <sub>1</sub> mm	l <sub>2</sub> mm	z	∇ a mm	d <sub>2</sub> Ø mm	B301
1/16	1.10	51	25	4	1.2	1.63	B3011/16 <sup>4)</sup>
5/64	1.50	51	25	4	1.6	2.03	B3015/64 <sup>4)</sup>
3/32	1.75	57	32	4	2.0	2.41	B3013/32 <sup>4)</sup>
7/64	2.03	64	38	4	2.2	2.82	B3017/64 <sup>4)</sup>
1/8	2.30	70	44	4	2.5	3.23	B3011/8 <sup>4)</sup>
9/64	2.64	73	48	4	2.8	3.63	B3019/64 <sup>4)</sup>
5/32	2.95	76	51	4	3.1	4.01	B3015/32 <sup>4)</sup>
11/64	3.23	89	57	4	3.6	4.42	B30111/64 <sup>4)</sup>
3/16	3.50	102	70	4	4.0	4.95	B3013/16 <sup>4)</sup>
7/32	4.13	102	70	6	4.5	5.59	B3017/32 <sup>4)</sup>
1/4	4.64	117	86	6	5.0	6.43	B3011/4 <sup>5)</sup>
9/32	5.23	143	105	6	5.6	7.42	B3019/32 <sup>5)</sup>
5/16	5.84	143	105	6	6.3	8.03	B3015/16 <sup>5)</sup>
11/32	6.43	152	114	6	7.1	8.81	B30111/32 <sup>5)</sup>
3/8	7.03	165	127	6	8.0	9.68	B3013/8 <sup>5)</sup>
13/32	7.42	191	146	6	8.0	10.46	B30113/32 <sup>5)</sup>
7/16	8.21	191	146	6	9.0	11.25	B3017/16 <sup>5)</sup>
1/2	9.41	210	165	6	10.0	12.85	B3011/2 <sup>5)</sup>

<sup>4)</sup> Limite di tolleranza +0.0040 / Toleranz +0.0030 / Tolerantie +0.0030 / Tolérance +0.0030

<sup>5)</sup> Limite di tolleranza +0.0050 / Toleranz +0.0050 / Tolerantie +0.0050 / Tolérance +0.0050