

## E002 E002TIN E003

- M Maschi a macchina Scanalature elicoidali 45°
- M Maschinen-Gewindebohrer, rechtsgedrallte Nuten 45°
- M Machinetap met gespiraliseerde spaangroeven 45°
- M Tarauds machine goujures hélicoidales 45°

Fornito in HSS-E fino a nuovo stoc



Lieferung in HSS-E bis neuer Lagerbestand verfügbar ist

Geleverd in HSS-E tot de nieuwe voorraad beschikbaar is

Fourni en HSS-E jusqu'à ce que le nouveau stock soit disponible

<b>E002</b>	▪	1.1	1.2	1.3	1.4	1.5	7.1	7.2	7.3	7.4	
	•	4.1	4.2	5.1	5.2						
<b>E002TIN</b>	▪	1.1	1.2	1.3	1.4	1.5	2.1	2.2	7.3	7.4	
	•	2.3	3.1	3.2	3.3	3.4	4.1	4.2	5.1	5.2	
<b>E003</b>	▪	1.1	1.2	1.3	1.4	1.5					
	•	2.1	2.2	2.3							

<b>E002</b>	M	ISO 529	6H		2.5XD	HSS-E PM	C 2-3	$\lambda 45^\circ$				
<b>E002TIN</b>	M	ISO 529	6H		2.5XD	HSS-E PM	C 2-3	$\lambda 45^\circ$		TIN		
<b>E003</b>	M	ISO 529	6H		2.5XD	HSS-E PM	C 2-3	$\lambda 45^\circ$		ST		



M	P mm	l <sub>1</sub> mm	l <sub>2</sub> mm	d <sub>2</sub> Ø mm	□ a mm	l <sub>3</sub> mm	z		l <sub>4</sub> mm	E002	E002TIN	E003
2	0.40	41	8	2.50	2.00	4	2	1.6	8	E002M2		E003M2
2.5	0.45	44.5	9.5	2.80	2.24	5	2	2.05	9.5	E002M2.5		E003M2.5
3	0.50	48	6	3.15	2.50	5	3	2.5	12.5	E002M3	E002TINM3	E003M3
4	0.70	53	7	4.00	3.15	6	3	3.3	19	E002M4	E002TINM4	E003M4
5	0.80	58	8	5.00	4.00	7	3	4.2	22	E002M5	E002TINM5	E003M5
6	1.00	66	10	6.30	5.00	8	3	5.0	27	E002M6	E002TINM6	E003M6
8	1.25	72	12	8.00	6.30	9	3	6.8	31	E002M8	E002TINM8	E003M8
10	1.50	80	15	10.00	8.00	11	3	8.5	35	E002M10	E002TINM10	E003M10
12	1.75	89	16	9.00	7.10	10	3	10.3	-	E002M12	E002TINM12	E003M12
14	2.00	95	18	11.20	9.00	12	3	12.0	-	E002M14		E003M14
16	2.00	102	18	12.50	10.00	13	4	14.0	-	E002M16	E002TINM16	E003M16
18	2.50	112	29	14.00	11.20	14	4	15.5	-	E002M18		E003M18
20	2.50	112	29	14.00	11.20	14	4	17.5	-	E002M20	E002TINM20	E003M20
22	2.50	118	29	16.00	12.50	16	4	19.5	-	E002M22		E003M22
24	3.00	130	35	18.00	14.00	18	4	21.0	-	E002M24		E003M24