

- ## R122
- Punta da centro - 120°
 - NC-Anbohrer, extra kurz - 120°
 - Extra korte NC-centerboor - 120°
 - Foret extra court de pointage NC - 120°

Affilatura a 4 facce fino a 10,0 mm
 4-Flächenanschliff bis 10 mm
 Viervlakspunt tot 10,0 mm
 Pointe à 4 facettes jusqu'au Ø 10,0 mm

- ## R123
- Punta da centro - 90°
 - NC-Anbohrer, extra kurz - 90°
 - Extra korte NC-centerboor - 90°
 - Foret extra court de pointage NC - 90°

Affilatura a 4 facce fino a 10,0 mm
 4-Flächenanschliff bis 10 mm
 Viervlakspunt tot 10,0 mm
 Pointe à 4 facettes jusqu'au Ø 10,0 mm

- ## R6011
- Punta da centro - 90°
 - NC-Anbohrer - 90°
 - NC-centerboor - 90°
 - Foret de pointage nc - 90°

Rivestimento TiAlN
 TiAlN beschichtet
 TiAlN gecoat
 Revêtu de TiAlN

| | | | | | | | | | | | | | | | | |
|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| R122; R123; R6011 | 1.1 | 1.2 | 1.3 | 1.4 | 1.5 | 1.6 | 1.7 | 1.8 | 2.1 | 2.2 | 3.1 | 3.2 | 3.3 | 3.4 | 4.1 | 4.2 |
| | 4.3 | 5.1 | 5.2 | 5.3 | 6.1 | 6.2 | 6.3 | 6.4 | 7.1 | 7.2 | 7.3 | 7.4 | 8.1 | 8.2 | | |

| | | | | | | | | | | |
|-------|----|--------|-----|------|-------|------------|---|--|--|--|
| R122 | HM | DORMER | 1XD | 120° | | | N | | | |
| R123 | HM | DORMER | 1XD | 90° | | | N | | | |
| R6011 | HM | DORMER | 1XD | 90° | TiAlN | DIN 6535HA | N | | | |



| | R122 | R123 | R6011 |
|---|--------------|--------------|--------------|
| | | | |
| | 5,00 - 20,00 | 5,00 - 20,00 | 6,00 - 16,00 |
| | R122 | R123 | R6011 |
| d ₁ Øh ₆ mm | | | |
| d ₁ decimal Inch | | | |
| l ₂ mm | | | |
| l ₁ mm | | | |
| 5.00 | R1225.0 | R1235.0 | |
| 6.00 | R1226.0 | R1236.0 | R60116.0 |
| 6.00 | R1228.0 | R1238.0 | |
| 8.00 | | | |
| 10.00 | | | R601110.0 |
| 10.00 | R12210.0 | R12310.0 | |
| 12.00 | R12212.0 | R12312.0 | |
| 16.00 | | | R601116.0 |
| 16.00 | R12216.0 | R12316.0 | |
| 20.00 | R12220.0 | R12320.0 | |