

# E021

- UNC Maschi a macchina imbocco corretto
- UNC Maschinen-Gewindebohrer, geradengetutet mit Schälanschnitt
- UNC Machinetap met schilaansnijding
- UNC Tarauds machine Coupe gun

Fornito in HSS-E fino a nuovo stoc  
 Lieferung in HSS-E bis neuer Lagerbestand verfügbar ist  
 Geleverd in HSS-E tot de nieuwe voorraad beschikbaar is  
 Fourni en HSS-E jusqu'à ce que le nouveau stock soit disponible

- E021 ■ 1.1 1.2 1.3 1.4 1.5  
 • 1.6 2.1 2.2 2.3 3.1 3.2 3.3 3.4

E021 **UNC** **ISO 529** **2B** **2.5XD** **HSS-E PM** **B 3.5-5**



UNC	TPI	d <sub>1</sub> nom mm	l <sub>1</sub> mm	l <sub>2</sub> mm	d <sub>2</sub> Ø mm	∠ a mm	l <sub>3</sub> mm	z		l <sub>4</sub> mm	E021
2	56	2.184	44.5	9.5	2.80	2.24	5	2	1.85	9.5	E0212-56
4	40	2.845	48	14	3.15	2.50	5	3	2.35	14	E0214-40
5	40	3.175	48	12.5	3.15	2.50	5	3	2.65	12.5	E0215-40
6	32	3.505	50	16	3.55	2.80	5	3	2.85	16	E0216-32
8	32	4.166	53	9.5	4.50	3.55	6	3	3.50	17	E0218-32
10	24	4.826	58	11	5.00	4.00	7	3	3.90	20	E02110-24
12	24	5.486	62	12	5.60	4.50	7	3	4.50	21	E02112-24
1/4	20	6.350	66	13	6.30	5.00	8	3	5.10	26	E0211/4
5/16	18	7.938	72	16	8.00	6.30	9	3	6.60	29	E0215/16
3/8	16	9.525	80	18	10.00	8.00	11	3	8.00	32	E0213/8
7/16	14	11.112	85	19	8.00	6.30	9	3	9.40	-	E0217/16
1/2	13	12.700	89	22	9.00	7.10	10	3	10.80	-	E0211/2
5/8	11	15.875	102	24	12.50	10.00	13	3	13.50	-	E0215/8
3/4	10	19.050	112	29	14.00	11.20	14	4	16.50	-	E0213/4
7/8	9	22.225	118	29	16.00	12.50	16	4	19.50	-	E0217/8
1"	8	25.400	130	35	18.00	14.00	18	4	22.25	-	E0211