

## S802HA

- Frese per cave
- Langlochfräser

## S802HB

- Spiebaanfrees
- Fraises à rainurer

S802HA; S802HB	▪	1.1	1.2	1.3	1.4	1.5	1.6	2.1	2.2	3.1	3.2	3.3	3.4	6.2	6.3	6.4	7.2	7.3	7.4	
	•	2.3	2.4	4.1	4.2	5.1	5.2	6.1	7.1	8.1	8.2									

S802HA	HM		N	Z 2		$\lambda 28^\circ$ $\gamma 9^\circ$	DIN 6535HA		
S802HB	HM		N	Z 2		$\lambda 28^\circ$ $\gamma 9^\circ$	DIN 6535HB		



d <sub>1</sub> Ø mm	Ch ±0.03x45° mm	d <sub>2</sub> Øh <sub>8</sub> mm	l <sub>2</sub> mm	l <sub>1</sub> mm	z	S802HA	S802HB
1.00	-	3	3	38	2	S802HA1.0	
1.50	-	3	3	38	2	S802HA1.5	
1.80	-	6	3	50	2	S802HA1.8	S802HB1.8
2.00	-	6	3	50	2	S802HA2.0	S802HB2.0
2.50	0.08	6	3	50	2	S802HA2.5	S802HB2.5
2.80	0.08	6	4	50	2	S802HA2.8	S802HB2.8
3.00	0.08	6	4	50	2	S802HA3.0	S802HB3.0
3.50	0.08	6	4	50	2	S802HA3.5	S802HB3.5
3.80	0.08	6	5	54	2	S802HA3.8	S802HB3.8
4.00	0.13	6	5	54	2	S802HA4.0	S802HB4.0
4.50	0.13	6	5	54	2	S802HA4.5	S802HB4.5
4.80	0.13	6	6	54	2	S802HA4.8	S802HB4.8
5.00	0.13	6	6	54	2	S802HA5.0	S802HB5.0
5.75	0.13	6	7	54	2	S802HA5.75	S802HB5.75
6.00	0.13	6	7	54	2	S802HA6.0	S802HB6.0
6.75	0.13	8	8	58	2	S802HA6.75	S802HB6.75
7.00	0.13	8	8	58	2	S802HA7.0	S802HB7.0
7.75	0.13	8	9	58	2	S802HA7.75	S802HB7.75
8.00	0.20	8	9	58	2	S802HA8.0	<sup>1)</sup> S802HB8.0
9.00	0.20	10	10	66	2	S802HA9.0	<sup>1)</sup> S802HB9.0
9.70	0.20	10	11	66	2	S802HA9.7	<sup>1)</sup> S802HB9.7
10.00	0.20	10	11	66	2	S802HA10.0	<sup>1)</sup> S802HB10.0
11.70	0.20	12	12	73	2	S802HA11.7	<sup>1)</sup> S802HB11.7
12.00	0.20	12	12	73	2	S802HA12.0	<sup>1)</sup> S802HB12.0
13.70	0.20	14	14	75	2	S802HA13.7	<sup>1)</sup> S802HB13.7
14.00	0.20	14	14	75	2	S802HA14.0	<sup>1)</sup> S802HB14.0
15.70	0.20	16	16	82	2	S802HA15.7	<sup>1)</sup> S802HB15.7
16.00	0.20	16	16	82	2	S802HA16.0	<sup>1)</sup> S802HB16.0
17.70	0.20	18	18	84	2	S802HA17.7	<sup>1)</sup> S802HB17.7
18.00	0.20	18	18	84	2	S802HA18.0	<sup>1)</sup> S802HB18.0
19.70	0.30	20	20	92	2	S802HA19.7	<sup>1)</sup> S802HB19.7
20.00	0.30	20	20	92	2	S802HA20.0	<sup>1)</sup> S802HB20.0

<sup>1)</sup> Ch ± 0.05x45° mm  
384