

- S803HA** • Frese per cave
• Langlochfräser
- S803HB** • Spiebaanfrees
• Fraises à rainurer

S803HA; S803HB	▪	1.1	1.2	1.3	1.4	1.5	1.6	2.1	2.2	3.1	3.2	3.3	3.4	6.2	6.3	6.4	7.2	7.3	7.4	
	•	2.3	2.4	4.1	4.2	5.1	5.2	6.1	7.1	8.1	8.2									

S803HA	HM		N	Z 3		$\lambda 28^\circ$ $\gamma 9^\circ$	DIN 6535HA	Alcrona			DIN 6527K
S803HB	HM		N	Z 3		$\lambda 28^\circ$ $\gamma 9^\circ$	DIN 6535HB	Alcrona			DIN 6527K



d_1 \emptyset mm	Ch $\pm 0.03 \times 45^\circ$ mm	d_2 $\emptyset h_6$ mm	l_2 mm	l_1 mm	z	S803HA	S803HB
1.00	-	3	3	38	3	S803HA1.0	
1.50	-	3	3	38	3	S803HA1.5	
1.80	-	6	3	50	3	S803HA1.8	S803HB1.8
2.00	-	6	3	50	3	S803HA2.0	S803HB2.0
2.50	0.08	6	3	50	3	S803HA2.5	S803HB2.5
2.80	0.08	6	4	50	3	S803HA2.8	S803HB2.8
3.00	0.08	6	4	50	3	S803HA3.0	S803HB3.0
3.50	0.08	6	4	50	3	S803HA3.5	S803HB3.5
3.80	0.08	6	5	54	3	S803HA3.8	S803HB3.8
4.00	0.13	6	5	54	3	S803HA4.0	S803HB4.0
4.50	0.13	6	5	54	3	S803HA4.5	S803HB4.5
4.80	0.13	6	6	54	3	S803HA4.8	S803HB4.8
5.00	0.13	6	6	54	3	S803HA5.0	S803HB5.0
5.75	0.13	6	7	54	3	S803HA5.75	S803HB5.75
6.00	0.13	6	7	54	3	S803HA6.0	S803HB6.0
6.75	0.13	8	8	58	3	S803HA6.75	S803HB6.75
7.00	0.13	8	8	58	3	S803HA7.0	S803HB7.0
7.75	0.13	8	9	58	3	S803HA7.75	S803HB7.75
8.00	0.20	8	9	58	3	S803HA8.0	S803HB8.0 ¹⁾
9.00	0.20	10	10	66	3	S803HA9.0	S803HB9.0 ¹⁾
9.70	0.20	10	11	66	3	S803HA9.7	S803HB9.7 ¹⁾
10.00	0.20	10	11	66	3	S803HA10.0	S803HB10.0 ¹⁾
11.70	0.20	12	12	73	3	S803HA11.7	S803HB11.7 ¹⁾
12.00	0.20	12	12	73	3	S803HA12.0	S803HB12.0 ¹⁾
13.70	0.20	14	14	75	3	S803HA13.7	S803HB13.7 ¹⁾
14.00	0.20	14	14	75	3	S803HA14.0	S803HB14.0 ¹⁾
15.70	0.20	16	16	82	3	S803HA15.7	S803HB15.7 ¹⁾
16.00	0.20	16	16	82	3	S803HA16.0	S803HB16.0 ¹⁾
17.70	0.20	18	18	84	3	S803HA17.7	S803HB17.7 ¹⁾
18.00	0.20	18	18	84	3	S803HA18.0	S803HB18.0 ¹⁾
19.70	0.30	20	20	92	3	S803HA19.7	S803HB19.7 ¹⁾
20.00	0.30	20	20	92	3	S803HA20.0	S803HB20.0 ¹⁾

¹⁾ Ch $\pm 0.05 \times 45^\circ$ mm