

R454


- Punta Force-X Serie lunga 5XD
- Force-X Spiralbohrer, lang 5XD
- Force-X Spiraalboor 5XD
- Foret série longue Force-X 5XD

R453

- Punta Force-X con fori di lubrificazione 5XD
- Force-X Spiralbohrer - Kühlkanal 5XD
- Force-X Spiraalboor met koelkanalen 5XD
- Foret Force-X - à trous d'huile 5XD

R454	▪	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2.1	2.2	2.3	3.1	3.2	3.3	3.4	6.1	6.2	6.3	7.1	7.2		
		7.3	7.4																				
	•	2.4	4.1	4.2	4.3	6.4																	
R453	▪	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2.1	2.2	3.1	3.2	3.3	3.4	4.1	4.2	4.3	6.1	6.2	6.3		
		6.4	7.1	7.2	7.3	7.4																	
	•	2.3	2.4																				

R454	HM	DIN 6537 L	5XD	140°	TiAIN	DIN 6535HA	CTW			
R453	HM	DIN 6537 L	5XD	140°	TiAIN	DIN 6535HA	CTW			



d_1 Ø Inch	d_1 Ø _{m7} mm	d_1 decimal Inch	l_2 mm	l_1 mm	l_3 mm	d_2 Ø _{h6} mm	R454	R453
	3.00	0.1181	28	66	36	6	R4543.0	R4533.0
	3.10	0.1220	28	66	36	6	R4543.1	R4533.1
1/8	3.18	0.1252	28	66	36	6	R4541/8	R4531/8
	3.20	0.1260	28	66	36	6	R4543.2	R4533.2
30	3.26	0.1283	28	66	36	6	R454N30	R453N30
	3.30	0.1299	28	66	36	6	R4543.3	R4533.3
	3.40	0.1339	28	66	36	6	R4543.4	R4533.4
29	3.45	0.1358	28	66	36	6	R454N29	R453N29
	3.50	0.1378	28	66	36	6	R4543.5	R4533.5
28	3.57	0.1406	28	66	36	6	R454N28	R453N28
9/64	3.57	0.1406	28	66	36	6	R4549/64	R4539/64
	3.60	0.1417	28	66	36	6	R4543.6	R4533.6
27	3.66	0.1441	28	66	36	6	R454N27	R453N27
	3.70	0.1457	28	66	36	6	R4543.7	R4533.7
26	3.73	0.1469	36	74	36	6	R454N26	R453N26
	3.80	0.1496	36	74	36	6	R4543.8	R4533.8
25	3.80	0.1496	36	74	36	6	R454N25	R453N25
24	3.86	0.1520	36	74	36	6	R454N24	R453N24
	3.90	0.1535	36	74	36	6	R4543.9	R4533.9
23	3.91	0.1539	36	74	36	6	R454N23	R453N23
5/32	3.97	0.1563	36	74	36	6	R4545/32	R4535/32
22	3.99	0.1571	36	74	36	6	R454N22	R453N22

d ₁ Ø Inch	d ₁ Øm, mm	d ₁ decimal Inch	l ₂ mm	l ₁ mm	l ₃ mm	d ₂ Øh _s mm	R454	R453
21	4.00	0.1575	36	74	36	6	R4544.0	R4534.0
	4.04	0.1591	36	74	36	6	R454N21	R453N21
	4.05	0.1594	36	74	36	6		R4534.05
20	4.09	0.1610	36	74	36	6	R454N20	R453N20
	4.10	0.1614	36	74	36	6	R4544.1	R4534.1
	4.20	0.1654	36	74	36	6	R4544.2	R4534.2
19	4.22	0.1661	36	74	36	6	R454N19	R453N19
	4.30	0.1693	36	74	36	6	R4544.3	R4534.3
	4.31	0.1697	36	74	36	6	R454N18	R453N18
11/64	4.37	0.1720	36	74	36	6	R45411/64	R45311/64
17	4.39	0.1728	36	74	36	6	R454N17	R453N17
	4.40	0.1732	36	74	36	6	R4544.4	R4534.4
	4.50	0.1772	36	74	36	6	R4544.5	R4534.5
16	4.50	0.1772	36	74	36	6	R454N16	R453N16
	4.57	0.1799	36	74	36	6	R454N15	R453N15
15	4.60	0.1811	36	74	36	6	R4544.6	R4534.6
	4.62	0.1819	36	74	36	6	R454N14	R453N14
	4.70	0.1850	36	74	36	6	R4544.7	R4534.7
13	4.70	0.1850	36	74	36	6	R454N13	R453N13
	3/16	4.76	0.1874	44	82	36	6	R4543/16
12	4.80	0.1890	44	82	36	6	R4544.8	R4534.8
	4.80	0.1890	44	82	36	6	R454N12	R453N12
11	4.85	0.1909	44	82	36	6	R454N11	R453N11
	4.90	0.1929	44	82	36	6	R4544.9	R4534.9
10	4.92	0.1937	44	82	36	6	R454N10	R453N10
	9	4.98	0.1961	44	82	36	6	R454N9
8	5.00	0.1969	44	82	36	6	R4545.0	R4535.0
	5.05	0.1988	44	82	36	6		R4535.05
	5.06	0.1992	44	82	36	6	R454N8	R453N8
7	5.10	0.2008	44	82	36	6	R4545.1	R4535.1
	5.11	0.2012	44	82	36	6	R454N7	R453N7
13/64	5.16	0.2031	44	82	36	6	R45413/64	R45313/64
6	5.18	0.2039	44	82	36	6	R454N6	R453N6
	5.20	0.2047	44	82	36	6	R4545.2	R4535.2
5	5.22	0.2055	44	82	36	6	R454N5	R453N5
	5.30	0.2087	44	82	36	6		R4535.3
4	5.31	0.2091	44	82	36	6	R454N4	R453N4
	5.40	0.2126	44	82	36	6		R4535.4
3	5.41	0.2130	44	82	36	6	R454N3	R453N3
	5.50	0.2165	44	82	36	6	R4545.5	R4535.5
7/32	5.56	0.2189	44	82	36	6	R4547/32	R4537/32
	5.60	0.2205	44	82	36	6	R4545.6	R4535.6
2	5.61	0.2209	44	82	36	6	R454N2	R453N2
	5.70	0.2244	44	82	36	6	R4545.7	R4535.7
1	5.79	0.2280	44	82	36	6	R454N1	R453N1
	5.80	0.2283	44	82	36	6	R4545.8	R4535.8
	5.90	0.2323	44	82	36	6		R4535.9
A	5.94	0.2339	44	82	36	6	R454A	R453A
	15/64	5.95	0.2343	44	82	36	6	R45415/64
B	6.00	0.2362	44	82	36	6	R4546.0	R4536.0
	6.03	0.2374	53	91	36	8	R454B	R453B
	6.05	0.2382	53	91	36	8		R4536.05
C	6.10	0.2402	53	91	36	8	R4546.1	R4536.1
	6.15	0.2421	53	91	36	8	R454C	R453C
D	6.20	0.2441	53	91	36	8	R4546.2	R4536.2
	6.25	0.2461	53	91	36	8	R454D	R453D
1/4	6.30	0.2480	53	91	36	8	R4546.3	R4536.3
	6.35	0.2500	53	91	36	8	R4541/4	R4531/4
E	6.35	0.2500	53	91	36	8	R454E	R453E
	6.40	0.2520	53	91	36	8	R4546.4	R4536.4
	6.50	0.2559	53	91	36	8	R4546.5	R4536.5
F	6.53	0.2571	53	91	36	8	R454F	R453F
	6.60	0.2598	53	91	36	8	R4546.6	R4536.6
G	6.63	0.2610	53	91	36	8	R454G	R453G
	6.70	0.2638	53	91	36	8	R4546.7	R4536.7
17/64	6.75	0.2657	53	91	36	8	R45417/64	R45317/64
H	6.76	0.2661	53	91	36	8	R454H	R453H
	6.80	0.2677	53	91	36	8	R4546.8	R4536.8
	6.90	0.2717	53	91	36	8	R4546.9	R4536.9

d ₁ Ø Inch	d ₁ Ø _m , mm	d ₁ decimal Inch	l ₂ mm	l ₁ mm	l ₃ mm	d ₂ Øh ₆ mm	R454	R453	
I	6.91	0.2720	53	91	36	8	R454I	R453I	
	7.00	0.2756	53	91	36	8	R4547.0	R4537.0	
J	7.04	0.2772	53	91	36	8	R454J	R453J	
	7.10	0.2795	53	91	36	8	R4547.1	R4537.1	
K	7.14	0.2811	53	91	36	8	R454K	R453K	
	9/32	7.14	0.2811	53	91	36	8	R4549/32	R4539/32
		7.20	0.2835	53	91	36	8		R4537.2
L		7.30	0.2874	53	91	36	8	R4547.3	R4537.3
		7.37	0.2902	53	91	36	8	R454L	R453L
		7.40	0.2913	53	91	36	8	R4547.4	R4537.4
M	7.49	0.2949	53	91	36	8	R454M	R453M	
		7.50	0.2953	53	91	36	8	R4547.5	R4537.5
19/64		7.54	0.2969	53	91	36	8	R45419/64	R45319/64
		7.60	0.2992	53	91	36	8	R4547.6	R4537.6
N		7.67	0.3020	53	91	36	8	R454N	R453N
		7.70	0.3031	53	91	36	8	R4547.7	R4537.7
		7.80	0.3071	53	91	36	8	R4547.8	R4537.8
		7.90	0.3110	53	91	36	8	R4547.9	R4537.9
5/16		7.94	0.3126	53	91	36	8	R4545/16	R4535/16
		8.00	0.3150	53	91	36	8	R4548.0	R4538.0
O		8.03	0.3161	61	103	40	10	R454O	R453O
		8.05	0.3169	61	103	40	10		R4538.05
		8.10	0.3189	61	103	40	10	R4548.1	R4538.1
		8.20	0.3228	61	103	40	10	R4548.2	R4538.2
P		8.20	0.3228	61	103	40	10	R454P	R453P
		8.30	0.3268	61	103	40	10		R4538.3
21/64		8.33	0.3280	61	103	40	10	R45421/64	R45321/64
		8.40	0.3307	61	103	40	10	R4548.4	R4538.4
Q		8.43	0.3319	61	103	40	10	R454Q	R453Q
		8.50	0.3346	61	103	40	10	R4548.5	R4538.5
		8.60	0.3386	61	103	40	10	R4548.6	R4538.6
R		8.61	0.3390	61	103	40	10	R454R	R453R
		8.70	0.3425	61	103	40	10	R4548.7	R4538.7
	11/32		8.73	0.3437	61	103	40	10	R45411/32
S		8.80	0.3465	61	103	40	10	R4548.8	R4538.8
		8.84	0.3480	61	103	40	10	R454S	R453S
		8.90	0.3504	61	103	40	10	R4548.9	R4538.9
T		9.00	0.3543	61	103	40	10	R4549.0	R4539.0
		9.09	0.3579	61	103	40	10	R454T	R453T
		9.10	0.3583	61	103	40	10	R4549.1	R4539.1
23/64		9.13	0.3594	61	103	40	10	R45423/64	R45323/64
		9.20	0.3622	61	103	40	10		R4539.2
		9.30	0.3661	61	103	40	10	R4549.3	R4539.3
U		9.35	0.3681	61	103	40	10	R454U	R453U
		9.40	0.3701	61	103	40	10	R4549.4	R4539.4
		9.50	0.3740	61	103	40	10	R4549.5	R4539.5
3/8		9.52	0.3748	61	103	40	10	R4543/8	R4533/8
V		9.58	0.3772	61	103	40	10	R454V	R453V
		9.60	0.3780	61	103	40	10	R4549.6	R4539.6
		9.70	0.3819	61	103	40	10	R4549.7	R4539.7
		9.80	0.3858	61	103	40	10	R4549.8	R4539.8
W		9.80	0.3858	61	103	40	10	R454W	R453W
		9.90	0.3898	61	103	40	10	R4549.9	R4539.9
25/64		9.92	0.3906	61	103	40	10	R45425/64	R45325/64
		10.00	0.3937	61	103	40	10	R45410.0	R45310.0
X		10.05	0.3957	70	118	45	12		R45310.05
		10.08	0.3969	70	118	45	12	R454X	R453X
		10.10	0.3976	70	118	45	12	R45410.1	R45310.1
		10.20	0.4016	70	118	45	12	R45410.2	R45310.2
Y		10.26	0.4039	70	118	45	12	R454Y	R453Y
		10.30	0.4055	70	118	45	12	R45410.3	R45310.3
13/32		10.32	0.4063	70	118	45	12	R45413/32	R45313/32
		10.40	0.4094	70	118	45	12	R45410.4	R45310.4
Z		10.49	0.4130	70	118	45	12	R454Z	R453Z
		10.50	0.4134	70	118	45	12	R45410.5	R45310.5
		10.60	0.4173	70	118	45	12	R45410.6	R45310.6
27/64		10.72	0.4220	70	118	45	12	R45427/64	R45327/64
		10.80	0.4252	70	118	45	12		R45310.8
		11.00	0.4331	70	118	45	12	R45411.0	R45311.0
7/16		11.11	0.4374	70	118	45	12	R4547/16	R4537/16

d ₁ Ø Inch	d ₁ Øm, mm	d ₁ decimal Inch	l ₂ mm	l ₁ mm	l ₃ mm	d ₂ Øh _s mm	R454	R453
	11.20	0.4409	70	118	45	12	R45411.2	R45311.2
	11.30	0.4449	70	118	45	12		R45311.3
	11.40	0.4488	70	118	45	12	R45411.4	R45311.4
	11.50	0.4528	70	118	45	12	R45411.5	R45311.5
29/64	11.51	0.4531	70	118	45	12	R45429/64	R45329/64
	11.60	0.4567	70	118	45	12	R45411.6	R45311.6
	11.80	0.4646	70	118	45	12	R45411.8	R45311.8
15/32	11.91	0.4689	70	118	45	12	R45415/32	R45315/32
	12.00	0.4724	70	118	45	12	R45412.0	R45312.0
	12.05	0.4744	76	124	45	14		R45312.05
	12.10	0.4764	76	124	45	14	R45412.1	
	12.20	0.4803	76	124	45	14	R45412.2	R45312.2
31/64	12.30	0.4843	76	124	45	14	R45431/64	R45331/64
	12.50	0.4921	76	124	45	14	R45412.5	R45312.5
	12.70	0.5000	76	124	45	14	R45412.7	R45312.7
1/2	12.70	0.5000	76	124	45	14	R4541/2	R4531/2
	12.80	0.5039	76	124	45	14	R45412.8	R45312.8
	13.00	0.5118	76	124	45	14	R45413.0	R45313.0
33/64	13.10	0.5157	76	124	45	14	R45433/64	R45333/64
	13.30	0.5236	76	124	45	14		R45313.3
17/32	13.49	0.5311	76	124	45	14	R45417/32	R45317/32
	13.50	0.5315	76	124	45	14	R45413.5	R45313.5
	13.80	0.5433	76	124	45	14	R45413.8	R45313.8
35/64	13.89	0.5469	76	124	45	14	R45435/64	R45335/64
	14.00	0.5512	76	124	45	14	R45414.0	R45314.0
	14.25	0.5610	82	133	48	16	R45414.25	R45314.25
9/16	14.29	0.5626	82	133	48	16	R4549/16	R4539/16
	14.50	0.5709	82	133	48	16	R45414.5	R45314.5
37/64	14.68	0.5780	82	133	48	16	R45437/64	R45337/64
	14.80	0.5827	82	133	48	16	R45414.8	R45314.8
	15.00	0.5906	82	133	48	16	R45415.0	R45315.0
19/32	15.08	0.5937	82	133	48	16	R45419/32	R45319/32
	15.10	0.5945	82	133	48	16	R45415.1	R45315.1
	15.30	0.6024	82	133	48	16		R45315.3
39/64	15.48	0.6094	82	133	48	16	R45439/64	R45339/64
	15.50	0.6102	82	133	48	16	R45415.5	R45315.5
	15.80	0.6220	82	133	48	16	R45415.8	R45315.8
5/8	15.88	0.6252	82	133	48	16	R4545/8	R4535/8
	16.00	0.6299	82	133	48	16	R45416.0	R45316.0
41/64	16.27	0.6406	91	143	48	18	R45441/64	R45341/64
	16.50	0.6496	91	143	48	18	R45416.5	R45316.5
21/32	16.67	0.6563	91	143	48	18	R45421/32	R45321/32
	17.00	0.6693	91	143	48	18	R45417.0	R45317.0
43/64	17.07	0.6720	91	143	48	18	R45443/64	R45343/64
11/16	17.46	0.6874	91	143	48	18	R45411/16	R45311/16
	17.50	0.6890	91	143	48	18	R45417.5	R45317.5
	17.80	0.7008	91	143	48	18	R45417.8	R45317.8
45/64	17.86	0.7031	91	143	48	18	R45445/64	R45345/64
	18.00	0.7087	91	143	48	18	R45418.0	R45318.0
23/32	18.26	0.7189	99	153	50	20	R45423/32	R45323/32
	18.50	0.7283	99	153	50	20	R45418.5	R45318.5
47/64	18.65	0.7343	99	153	50	20	R45447/64	R45347/64
	19.00	0.7480	99	153	50	20	R45419.0	R45319.0
3/4	19.05	0.7500	99	153	50	20	R4543/4	R4533/4
	19.50	0.7677	99	153	50	20	R45419.5	R45319.5
	19.80	0.7795	99	153	50	20	R45419.8	R45319.8
	20.00	0.7874	99	153	50	20	R45420.0	R45320.0