

# P803

- Lime rotative - cilindrico con spallamento
- Frässtift- Zylinder mit Stirverzahnung
- Stiftrees - Cilindrisch met kopvertanding
- Lime rotative - Cylindrique avec coupe en bout

brasato su 6,00 mm  
 Gelötet, wenn der Kopfdurchmesser größer 6 mm ist  
 > Ø 6mm gesoldeerd  
 Brasée au-dessus de 6,00 mm

# P803C

P803; P803C

1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	2.1	2.2	2.3	2.4	3.1	3.2	3.3	3.4	4.1	4.2
4.3	5.1	5.2	5.3	6.2	6.3	6.4	9.1										
6.1																	

P803

HM

B



DC



P803C

HM

B



DC



P803



3.00 - 16.00

P803C



3.00 - 12.70

d <sub>1</sub> Ø mm	d <sub>2</sub> Øh <sub>7</sub> mm	l <sub>2</sub> mm	l <sub>1</sub> mm	P803	P803C
3.00	3	14	38	P8033.0X3.0 <sup>1)</sup>	P803C3.0X3.0 <sup>1)</sup>
6.30	3	12.7	45	P8036.3X3.0	
6.00	6	18	50	P8036.0X6.0 <sup>1)</sup>	P803C6.0X6.0 <sup>1)</sup>
8.00	6	19	64	P8038.0X6.0	P803C8.0X6.0
9.60	6	19	64	P8039.6X6.0	P803C9.6X6.0
12.70	6	25	70	P80312.7X6.0	P803C12.7X6.0
16.00	6	25	70	P80316.0X6.0	

<sup>1)</sup> d2 tolleranza h6 / d2 toleranz h6 / d2 tolerantie h6 / d2 tolérance h6