

Maschi STI per candele a gradino corto per filetti riportati ISO 2 (6H)

Passo Metrico



HSS-G Tolleranza ISO 1 (4H)

M

Diametro Nominale D	P	B1	B2	L 3	L 2	L1	D 2	☐	Articolo
M 6	x 1.0	7.3	6	7	28	70	8	6.3	03630
M 8	x 1.25	9.6	8	9	32	75	8	6.3	03631
M 10	x 1.5	11.9	10	9	37	80	9	7.1	03632
M 10	x 1.25	11.6	10	8	30	74	8	6.3	03637
M 10	x 1.0	11.3	10	8	30	74	8	6.3	03633
M 12	x 1.25	13.6	12	9	32	75	9	7.1	03634
M 14	x 1.25	15.6	14	10	45	90	12	9.2	03635
M 18	x 1.5	20.0	18	10	47	116	16	12.5	03636

Punte da trapano STI per Filetti Riportati



Diametro Ø	PER FILETTI	Articolo
---------------	-------------	----------

Metrico

2.1 mm	M 2 X 0.4	VC 021
2.4 mm	UNC 2 X 56	VC 024
2.6 mm	M 2.5 X 0.45	VC 026
3.0 mm	UNC 4 X 40 - UNF 4 X 48	VC 030
3.2 mm	M 3 X 0.5	VC 032
3.4 mm	UNC 5 X 40 - BSW 1/8 X 40	VC 034
3.7 mm	M 3.5 X 0.6	VC 037
4.2 mm	M4 X 0.7	VC 042
4.4 mm	UNC 8 X 32 - UNF 8 X 36	VC 044
4.5 mm	BSF 3/16 X 32	VC 045
5.0 mm	UNC 10 X 24 - UNF 10 X 32 - BSW 3/16 X 24	VC 050
5.1 mm	UNC 10 X 24 - UNF 10 X 32 - BSW 3/16 X 24	VC 051
5.2 mm	M 5 X 0.8	VC 052
6.0 mm		VC 060
6.3 mm	M 6 X 1.0	VC 063
6.6 mm	UNF 1/4 X 28 - BSF 1/4 X 26	VC 066
6.7 mm	UNC 1/4 X 20 - BSW 1/4 X 20	VC 067
7.3 mm	M 7 X 1.0	VC 073
8.3 mm	M 8 X 1.25 - M 8 X 1.0	VC 083
9.3 mm	M 9 X 1.25	VC 093
9.8 mm	UNF 3/8 X 24	VC 098
9.9 mm	UNC 3/8 X 16 - BSW 3/8 X 16 - BSF 3/8 X 20	VC 099
10.3 mm	M 10 X 1.25 - M 10 X 1.0	VC 103
10.4 mm	M 10 X 1.5	VC 104
11.4 mm	M 11 X 1.5	VC 114
11.5 mm	UNF 7/16 X 20	VC 115
11.6 mm	UNC 7/16 X 14 - BSW 7/16 X 14 - BSF 7/6 X 18	VC 116
12.3 mm	M 12 X 1.25 - M 12 X 1.0	VC 123
12.4 mm	M 12 X 1.75 - M 12 X 1.5	VC 124
13.0 mm	UNC 1/2 X 13 - UNF 1/2 X 12 BSW 1/2 X 12 - BSF 1/2 X 16	VC 130