


# Inserti Phillips®



C 6,35

E 6.35

GERMANY



## CONIATO DUREZZA 59 - 63 HRC - TORSION

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
12041	PH 1	25	10
12041 B	PH 1	25	BOX 200
12041 BX	PH 1	25	BOX 500
12041 BXL	PH 1	25	BOX 1000
12042	PH 2	25	10
12042 B	PH 2	25	BOX 200
12042 BX	PH 2	25	BOX 500
12042 BXL	PH 2	25	BOX 1000
12044	PH 3	25	10
12044 B	PH 3	25	BOX 200
12044 BX	PH 3	25	BOX 500
12044 BXL	PH 3	25	BOX 1000

MAGNETICI



## INSERTI PHILLIPS MAGNETICI, CON NUOVO MAGNETE DI TESTA PER TRATTENERE LE VITI

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
812041	PH 1	25	10
812042	PH 2	25	10
812044	PH 3	25	10

TITANIO



## CONIATO RIVESTITO TITANIO

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
212041 <b>TIN</b>	PH 1	25	10
212041 <b>TIN B</b>	PH 1	25	BOX 100
212042 <b>TIN</b>	PH 2	25	10
212042 <b>TIN B</b>	PH 2	25	BOX 100
212044 <b>TIN</b>	PH 3	25	10
212044 <b>TIN B</b>	PH 3	25	BOX 100

GERMANY




## FRESATO DUREZZA 59 - 63 HRC

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
12040	PH 0	25	10
12037	PH 1	25	10
12037 B	PH 1	25	BOX 200
12038	PH 2	25	10
12038 B	PH 2	25	BOX 200
12039	PH 3	25	10
12039 B	PH 3	25	BOX 200
nota: <b>MAGGIORATO</b>			
12045	PH 4	32	10

GERMANY



## FRESATO DUREZZA 59 - 63 HRC

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
12046	PH 1	50	10
12047	PH 2	50	10
12050	PH 3	50	10

GERMANY



## FRESATO RIVESTITO TITANIO

 attacco: DIN 3126, E 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
213021 <b>TIN</b>	PH 1	50	5
213022 <b>TIN</b>	PH 2	50	5
213023 <b>TIN</b>	PH 3	50	5
2135021 <b>TIN</b>	PH 1	70	5
2135022 <b>TIN</b>	PH 2	70	5
2135023 <b>TIN</b>	PH 3	70	5
2136021 <b>TIN</b>	PH 1	90	5
2136022 <b>TIN</b>	PH 2	90	5
2136023 <b>TIN</b>	PH 3	90	5

TITANIO

COLOR



## INSERTI PHILLIPS COLORATI

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
512041	PH 1	25	10
512042	PH 2	25	10
512044	PH 3	25	10

IMPACT



## INSERTO "IMPACT" RESISTE ALLE SOLLECITAZIONI DEGLI AVVITATORI AD IMPATTO

 attacco: DIN 3126, C 6,35 - E 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo		L mm	
2062	PH 2	25	1
2062 B	PH 2	25	BOX 100
32062	<b>NEW</b> PH 2	50	1

USA



## TORSION - RIVESTITO TITANIO 60-63 HRC

 attacco: DIN 3126, C 6,35  
 impronta: DIN 5260, PH

FEWMEC articolo	mm	L mm	
60430	PH 1	25	10
60431	PH 2	25	10
60432	PH 3	25	10

TITANIO