




TESTA SFERICA ALTA QUALITÀ

attacco: DIN 3126, C 6,35
impronta: ESAGONO

articolo	mm	L mm	
110-2,5 KK	2,5	25	10
110-3 KK	3	25	10
110-4 KK	4	25	10
110-5 KK	5	25	10
110-6 KK	6	25	10
110-8 KK	8	25	10



TESTA SFERICA ALTA QUALITÀ

attacco: DIN 3126, E 6,35
impronta: ESAGONO

articolo	mm	L mm	
167-2 KK	2	50	5
167-2,5 KK	2,5	50	5
167-3 KK	3	50	5
167-4 KK	4	50	5
167-5 KK	5	50	5
167-6 KK	6	50	5
167-7 KK	7	50	5
167-8 KK	8	50	5
1167-2,5 KK	2,5	70	5
1167-3 KK	3	70	5
1167-4 KK	4	70	5
1167-5 KK	5	70	5
1167-6 KK	6	70	5
1167-7 KK	7	70	5
1167-8 KK	8	70	5
1267-3 KK	3	90	5
1267-4 KK	4	90	5
1267-5 KK	5	90	5
1267-6 KK	6	90	5
1267-8 KK	8	90	5
3167-3 KK	3	150	5
3167-4 KK	4	150	5
3167-5 KK	5	150	5
3167-6 KK	6	150	5
3167-8 KK	8	150	5



MISURE IN POLLICI

attacco: DIN 3126, C 6,35
impronta: ESAGONO

articolo	pollici	L mm	
27095	1/16"	32	5
27096	5/64"	25	5
27097	3/32"	25	5
37475	7/64"	25	5
27098	1/8"	25	5
37476	9/64"	25	5
27099	5/32"	25	5
27100	3/16"	25	5
27101	7/32"	25	5
27102	1/4"	25	5
27103	5/16"	25	5



MISURE IN POLLICI

attacco: DIN 3126, E 6,35
impronta: ESAGONO

articolo	pollici	L mm	
27420	1/16"	50	5
27421	5/64"	50	5
27422	3/32"	50	5
37563	7/64"	50	5
27423	1/8"	50	5
37565	9/64"	50	5
27424	5/32"	50	5
27425	3/16"	50	5
27426	7/32"	50	5
27427	1/4"	50	5

Inserti Brugola c/foro



ESAGONO C/FORO PER VITI DI SICUREZZA

attacco: DIN 3126, C 6,35
impronta: ESAGONO CON FORO

articolo	mm	L mm	
12320	2	25	5
12325	2,5	25	5
12330	3	25	5
12340	4	25	5
12350	5	25	5
12360	6	25	5
12380	8	25	5
12390	10	25	5



ESAGONO C/FORO PER VITI DI SICUREZZA

attacco: DIN 3126, E 6,35
impronta: ESAGONO CON FORO

articolo	mm	L mm	
13641	2	50	5
13642	2,5	50	5
13643	3	50	5
13644	4	50	5
13645	5	50	5
13646	6	50	5
13648	8	50	5
13649	10	50	5
113641	2	75	5
113642	2,5	75	5
113643	3	75	5
113644	4	75	5
113645	5	75	5
113646	6	75	5
113648	8	75	5
113649	10	75	5

