


IMPIEGHI GENERICI

GENERAL PURPOSE

TOUS USAGES

ALLZWECK-HYDRAULIKZYLINDER

CE Made in Italy



Ritorno a gravità
Load return
Retour sous charge
Lastrückzug



Ritorno a molla
Spring return
Retour par ressort
Federrückzug

OPTIONAL Pag. 321

ART.	TON	Pressione Pressure Pression Druck	Capacità olio Oil capacity Capacité huile Ölvolumen	A mm	B mm	C mm	D mm	KG
359/B	5	640 bar	52,8 cm ³	155	100	55	30	1
359/C	5	640 bar	72 cm ³	195	120	75	30	1,2
359/D	5	640 bar	100,8 cm ³	255	150	105	30	1,5
360/B	10	640 bar	87,4 cm ³	155	100	55	40	1,6
360/C	10	640 bar	119,2 cm ³	195	120	75	40	1,9
360/D	10	640 bar	167 cm ³	255	150	105	40	2,4
361/B	20	640 bar	132,4 cm ³	145	105	40	60	4,1
361/C	20	640 bar	198,6 cm ³	185	125	60	60	4,9
361/D	20	640 bar	331 cm ³	265	165	100	60	6,5
362/B	30	640 bar	200,8 cm ³	145	105	40	75	5,6
362/C	30	640 bar	301,2 cm ³	185	125	60	75	6,8
362/D	30	640 bar	502 cm ³	265	165	100	75	9,2
363/B	50	640 bar	274,7 cm ³	140	105	35	90	9,2
363/C	50	640 bar	431,7 cm ³	180	125	55	90	11
363/D	50	640 bar	745,7 cm ³	260	165	95	90	15,2

ART.	TON	Pressione Pressure Pression Druck	Capacità olio Oil capacity Capacité huile Ölvolumen	A mm	B mm	C mm	D mm	KG
359/BM	5	640 bar	52,8 cm ³	155	100	55	30	1
359/CM	5	640 bar	72 cm ³	195	120	75	30	1,2
359/DM	5	640 bar	100,8 cm ³	255	150	105	30	1,5
360/BM	10	640 bar	87,4 cm ³	155	100	55	40	1,6
360/CM	10	640 bar	119,2 cm ³	195	120	75	40	1,9
360/DM	10	640 bar	167 cm ³	255	150	105	40	2,4
361/BM	20	640 bar	132,4 cm ³	145	105	40	60	4,1
361/CM	20	640 bar	198,6 cm ³	185	125	60	60	4,9
361/DM	20	640 bar	331 cm ³	265	165	100	60	6,5
362/BM	30	640 bar	200,8 cm ³	145	105	40	75	5,6
362/CM	30	640 bar	301,2 cm ³	185	125	60	75	6,8
362/DM	30	640 bar	502 cm ³	265	165	100	75	9,2
363/BM	50	640 bar	274,7 cm ³	140	105	35	90	9,2
363/CM	50	640 bar	431,7 cm ³	180	125	55	90	11
363/DM	50	640 bar	745,7 cm ³	260	165	95	90	15,2