Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 9.0 Ah capacity, for long service life. Light and powerful, for approx. 80 1" steel pipe cuts with guide holder or approx. 135 1" steel pipe cuts without guide holder with one battery charge. Graduated charging state display with coloured LED. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger Li-Ion 230 V, 50–60 Hz, 90 W. Rapid charger Li-Ion 230 V, 50–60 Hz, 300 W, for shorter charging times, as accessory. Li-Ion 230 V/21.6 V, 70 A voltage supply for mains operation 230 V instead of Li-Ion battery 21.6 V, as accessory.

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Supply format

REMS Akku-Tiger 22 V VE Set. Cordless pipe reciprocating saw with Vario Electronics (VE) for effortless, fast, right-angled sawing with guide holder and for free-hand sawing. Drive unit with spade handle, maintenance-free, water and dust proof oscillation drive with all-round needle bearing crank drive (ANC), aggressive orbital stroke, powerful 21.6V, 500 W battery motor, safety switch. Continuous, electronic stroke speed control (accelerator switch) 0 to 1900 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6V, 9.0Ah battery, Li-Ion 230V, 50–60 Hz, 90W rapid charger. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

_ poor remove opposition out bladded _ remove out of the control out o		
	ArtNo.	
	560053	

Other voltages on request.



Accessories

Description	ArtNo.
REMS Akku-Tiger 22 V VE drive unit, without battery	560011
REMS saw blades see page 68-69.	
Guide support 2", for pipes Ø 1/8−2"	563000
Battery Li-lon 21.6 V, 9.0 Ah	571583
Rapid charger Li-lon 230 V, 50-60 Hz, 90 W	571585
Rapid charger Li-lon 230 V, 50-60 Hz, 300 W	571587
Voltage supply 230 V/21.6 V, 70 A, for mains	
operation 230 V instead of battery Li-lon 21.6 V	571578
Steel case with inlay	566030

